



TECHNICAL SPECIFICATIONS			
<b>MAXIMUM SUSPENDING LOAD</b> (SL = P <sub>R</sub> + P <sub>SLING</sub> + P <sub>PLAT</sub> + P <sub>LCU</sub> )	SL max	620	720 kg
<b>RATED LOAD</b> (SUGGESTIVE)	PR max	350	450 kg
<b>PIT DEPTH</b>	PD min	220	mm
<b>HEADROOM</b>	HD min	2200	mm
<b>PLATFORM DIMENSIONS</b>	WIDTH	A max	1250 mm
	DEPTH	B max	1100 mm
<b>GUIDE TYPE</b>	70 x 70 x 9		
<b>SAFETY GEAR TYPE</b>	INSTANTANEOUS		
<b>PISTON TYPE</b>	(depending on load and travel)	Φ50 M	Φ60 M
<b>PUMP TYPE</b>	(depending on piston type)	8	13 lt/min
<b>OIL TANK</b>	T50		
<b>MOTOR TYPE</b>	(230 volts 1PH)	1,8	KW
	(400 volts 3PH)	2,0	KW
<b>CAR SPEED</b>	V max	0,15	m/s
<b>CAR TRAVEL</b>	TR max	7.000	10.000 mm
<b>NUMBER OF STOPS</b>	max	4	
<b>DOORS TYPE</b>	SEMI-AUTOMATIC		

